

***** Replacement part ***** SIMATIC S7-400H, CPU 417H
 Central processing unit for S7-400H 4 interfaces: 1 MPI/DP, 1 DP
 and 2 for sync modules 30 MB memory (15 MB data/15 MB program)



Figure similar

General information	
Product type designation	CPU 417H
HW functional status	1
Firmware version	V4.5
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.3 SP2 or higher with HW update
CiR - Configuration in RUN	
CiR synchronization time, basic load	60 ms
CiR synchronization time, time per I/O byte	10 μ s
Supply voltage	
Rated value (DC)	No; Power supply via system power supply
<ul style="list-style-type: none"> 24 V DC 	
Input current	
from backplane bus 5 V DC, typ.	1.5 A
from backplane bus 5 V DC, max.	1.8 A
from backplane bus 24 V DC, max.	150 mA; Per DP interface

from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	6.5 W
Memory	
Type of memory	other
Work memory	
<ul style="list-style-type: none"> • integrated • integrated (for program) • integrated (for data) • expandable 	<ul style="list-style-type: none"> 30 Mbyte 15 Mbyte 15 Mbyte No
Load memory	
<ul style="list-style-type: none"> • expandable FEPRM • expandable FEPRM, max. • integrated RAM, max. • expandable RAM • expandable RAM, max. 	<ul style="list-style-type: none"> Yes 64 Mbyte 256 kbyte Yes 64 Mbyte
Backup	
<ul style="list-style-type: none"> • present • with battery • without battery 	<ul style="list-style-type: none"> Yes Yes; all data No
Battery	
Backup battery	
<ul style="list-style-type: none"> • Backup current, typ. • Backup current, max. • Backup time, max. • Feeding of external backup voltage to CPU 	<ul style="list-style-type: none"> 970 μA; Valid up to 40°C 1 980 μA Dealt with in the module data manual with the secondary conditions and the factors of influence 5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	0.018 μ s
for word operations, typ.	0.018 μ s
for fixed point arithmetic, typ.	0.018 μ s
for floating point arithmetic, typ.	0.054 μ s
CPU-blocks	
DB	
<ul style="list-style-type: none"> • Number, max. • Size, max. 	<ul style="list-style-type: none"> 8 191; Number range: 1 - 8191 64 kbyte
FB	
<ul style="list-style-type: none"> • Number, max. • Size, max. 	<ul style="list-style-type: none"> 6 144; Number range: 0 - 6143 64 kbyte
FC	

• Number, max.	6 144; Number range: 0 - 6143
• Size, max.	64 kbyte
OB	
• Size, max.	64 kbyte
• Number of time alarm OBs	8
• Number of delay alarm OBs	4
• Number of cyclic interrupt OBs	9
• Number of process alarm OBs	8
Nesting depth	
• per priority class	24
• additional within an error OB	2
Counters, timers and their retentivity	
S7 counter	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
S7 times	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
retentive data area in total	Total working and load memory (with backup battery)
Flag	

• Number, max.	16 kbyte
• Retentivity available	Yes
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; in 1 memory byte
Local data	
• adjustable, max.	64 kbyte
• preset	32 kbyte
Address area	
I/O address area	
• Inputs	16 kbyte
• Outputs	16 kbyte
Process image	
• Inputs, adjustable	16 kbyte
• Outputs, adjustable	16 kbyte
• Inputs, default	1 024 byte
• Outputs, default	1 024 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	131 072
— of which central	131 072
• Outputs	131 072
— of which central	131 072
Analog channels	
• Inputs	8 192
— of which central	8 192
• Outputs	8 192
— of which central	8 192
Hardware configuration	
Number of expansion units, max.	21
connectable OPs	63 without message processing, 16 with message processing
Multicomputing	No
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; Single mode only
Number of DP masters	
• integrated	2
• via CP	10

• Mixed mode IM + CP permitted	No
Number of operable FMs and CPs (recommended)	
• FM	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
• CP, PtP	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
• PROFIBUS and Ethernet CPs	14; Of which max. 10 CP as DP master
Slots	
• required slots	2
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
• Deviation per day (buffered), max.	1.7 s; Power off
• Deviation per day (unbuffered), max.	8.6 s; Power on
Operating hours counter	
• Number	8
• Number/Number range	0 to 7
• Range of values	0 to 32767 hours
• Granularity	1 h
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
Time difference in system when synchronizing via	
• MPI, max.	200 ms
Interfaces	
Number of RS 485 interfaces	2
Number of other interfaces	0
Optical interface	No
1. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS + MPI
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA

Protocols	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
MPI	
• Number of connections	44
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
• Number of connections, max.	32
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	No
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	No
— Direct data exchange (slave-to-slave communication)	No
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte

2. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS + MPI
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	32
Protocols	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
PROFIBUS DP master	
• Number of connections, max.	32
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— Equidistance	No
— SYNC/FREEZE	No
— Direct data exchange (slave-to-slave communication)	No
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP slave	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
3. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization submodule IF 960 6ES7960-1AA04-0XA0 or 6ES7960-1AB04-0XA0
4. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization submodule IF 960 6ES7960-1AA04-0XA0 or 6ES7960-1AB04-0XA0
Communication functions	

PG/OP communication	Yes
<ul style="list-style-type: none"> • Number of connectable OPs without message processing 	63
<ul style="list-style-type: none"> • Number of connectable OPs with message processing 	16
Global data communication	
<ul style="list-style-type: none"> • supported 	No
S7 basic communication	
<ul style="list-style-type: none"> • supported 	No
S7 communication	
<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • as server 	Yes
<ul style="list-style-type: none"> • as client 	Yes
<ul style="list-style-type: none"> • User data per job, max. 	64 kbyte
<ul style="list-style-type: none"> • User data per job (of which consistent), max. 	462 byte; 1 variable
S5 compatible communication	
<ul style="list-style-type: none"> • supported 	Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV)
<ul style="list-style-type: none"> • User data per job, max. 	8 kbyte
<ul style="list-style-type: none"> • User data per job (of which consistent), max. 	240 byte
<ul style="list-style-type: none"> • Number of simultaneous AG-SEND/AG-RECV orders per CPU, max. 	64/64
Standard communication (FMS)	
<ul style="list-style-type: none"> • supported 	Yes; Via CP and loadable FB
Number of connections	
<ul style="list-style-type: none"> • overall 	64
<ul style="list-style-type: none"> • usable for PG communication <ul style="list-style-type: none"> — reserved for PG communication 	1
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — adjustable for PG communication, max. 	0
<ul style="list-style-type: none"> • usable for OP communication <ul style="list-style-type: none"> — reserved for OP communication 	1
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — adjustable for OP communication, max. 	0
<ul style="list-style-type: none"> • usable for S7 basic communication <ul style="list-style-type: none"> — reserved for S7 basic communication 	0
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — adjustable for S7 basic communication, max. 	0
<ul style="list-style-type: none"> • usable for S7 communication <ul style="list-style-type: none"> — reserved for S7 communication 	0
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — adjustable for S7 communication, max. 	0
<ul style="list-style-type: none"> • usable for routing <ul style="list-style-type: none"> — reserved for routing 	0
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — adjustable for routing, max. 	0
S7 message functions	

Number of login stations for message functions, max.	16
Symbol-related messages	No
Program alarms	Yes
simultaneously active Alarm-S blocks, max.	200
Alarm 8-blocks	Yes
• Number of instances for alarm 8 and S7 communication blocks, max.	10 000
• preset, max.	1 200
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	64

Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	4

Status/control

• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
• Number of variables, max.	70

Forcing

• Forcing	Yes
• Forcing, variables	Inputs/outputs, bit memories, distributed I/Os
• Number of variables, max.	512

Diagnostic buffer

• present	Yes
• Number of entries, max.	3 200
— adjustable	Yes
— preset	120

Configuration

Configuration software

• STEP 7	Yes
----------	-----

Programming

• Command set	see instruction list
• Nesting levels	8
• Access to consistent data in process image	Yes
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list

Programming language

— LAD	Yes
— FBD	Yes
— STL	Yes

— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes

Number of simultaneously active SFCs

— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8
— RDSYSST	8
— DP_TOPOL	1

Number of simultaneously active SFBs

— RDREC	8
— WRREC	8

Know-how protection

- User program protection/password protection Yes

Dimensions

Width	50 mm
Height	290 mm
Depth	219 mm

Weights

Weight, approx.	995 g
-----------------	-------

last modified: 10/29/2020