

\*\*\*Spare part\*\*\* SIMATIC DP, Connection ET 200M IM 153-2 High Feature for max. 12 S7-300 modules with redundancy capability, Timestamping suitable for isochronous mode New features: up to 12 modules can be used Slave INITIATIVE for Drive ES and Switch ES Expanded quantity structure for HART auxiliary variables Operation of the 64-channel modules 32 signals/slot



Figure similar

General information	
Product type designation	IM 153-2 DP HF
Vendor identification (VendorID)	801Eh
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	600 mA
Inrush current, typ.	3 A
$I^2t$	0.1 A <sup>2</sup> ·s
Output voltage	

Rated value (DC)	5 V
<b>Output current</b>	
for backplane bus (5 V DC), max.	1.5 A
<b>Power loss</b>	
Power loss, typ.	5.5 W
<b>Address area</b>	
<b>Addressing volume</b>	
• Inputs	244 byte
• Outputs	244 byte
<b>Hardware configuration</b>	
Number of modules per DP slave interface, max.	12
<b>Time stamping</b>	
Accuracy	1 ms; 1 ms at up to 8 modules; 10 ms at up to 12 modules
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting
<b>Interfaces</b>	
Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s
<b>1. Interface</b>	
automatic detection of transmission rate	Yes
<b>Interface types</b>	
• Output current of the interface, max.	70 mA
• Design of the connection	9-pin sub D socket
<b>PROFIBUS DP slave</b>	
• GSD file	SI04801.GSG
• automatic baud rate search	Yes
<b>Protocols</b>	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
<b>Protocols (Ethernet)</b>	
• TCP/IP	No
<b>PROFIBUS DP</b>	
• Number of node addresses, max.	1 to 125 permitted
<b>Services</b>	
— SYNC capability	Yes

— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes; Sender

#### Potential separation

Potential separation exists	Yes
-----------------------------	-----

#### Isolation

Isolation tested with	Isolation voltage 500 V
-----------------------	-------------------------

#### Degree and class of protection

IP degree of protection	IP20
-------------------------	------

#### Ambient conditions

##### Ambient temperature during operation

- |        |       |
|--------|-------|
| • min. | 0 °C  |
| • max. | 60 °C |

##### Altitude during operation relating to sea level

- |   |         |
|---|---------|
| • Installation altitude above sea level, max. | 3 000 m |
|---|---------|

#### Configuration

##### Configuration software

- |          |   |
|----------|---|
| • STEP 7 | Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file |
|----------|---|

#### Dimensions

Width	40 mm
Height	125 mm
Depth	117 mm

#### Weights

Weight, approx.	360 g
-----------------	-------

**last modified:** 12/10/2020